For more information please go to WWW.P65WARNINGS.CA.GOV

birth defects or other reproductive harm.

State of California to cause cancer and

This product can expose you to chemicals including Lead and Di(2-ethylhexyl) phthalate (DEHP) which are known to the

construction. • Large capacity outer tube for heavy rainfall collection.

Inner tube measures in 0.5 mm or 1/100ths

of an inch increment.

- Long-life sun hardy UV stabilized plastic
- Rain collection capacity of inner tube 25 mm/1 inch.
- Total collection capacity 250mm/10 inches.

• Easy to read display (inches and mm)

Frost resistant material

The Adir Pro Rain Gauge is designed to accommodate the standardized design used throughout the world for official rainfall measurements as determined by the National Weather Service.

Features:

Checking the Rain Gauge:

- measurement. the Inner Tube(B) to view and record the 1. Remove the rain Funnel Lid (C) and take out
- .9duj - Then empty the rainwater out of the
- rainwater into the Inner Tube(B) to measure slide it out of the mounting brackets, tip the 2. If the Outer Tube (A) has also collected rain,
- si (A) 9duT return the Outer Tube(A) is and repeat the process until all the 3. Record the measurement, empty the tube the collected amount.
- into the mounting brackets and then put and recorded, place the Outer Tube(A) back 4. Once all the rainwater has been measured measured and recorded.

the Inner Tube (B) and Funnel Lid (C) back.

Caring for your Rain Gauge:

- properly maintained. · Your rain gauge should last for many years if
- detergent and water to clean it gently. For cleaning your rain gauge, use a mild
- Do not use harsh abrasives or solvents.
- gauge, or you risk it breaking. Do not allow water to freeze inside the rain

ADIPR500-01-BLK

27 Selvage Street • Irvington, NJ • 07111

© 2021 AdirCorp

adircorp.com

For Optimal Readings:

- .19.5 feet apart. install a pair of rain gauges at least To achieve the most accurate readings,
- your results. ensuring wind or other factors don't skew you can take the two readings' average, When utilizing more than one rain gauge,

.llainia Rainfall:

- taking a measurement. Collect rain for a total of 24 hours before
- the same time every day. evaporation from occurring, repeat this at preferably in the morning to prevent Once you take the first measurement,

you jeopardize the integrity of the brackets and ensure not to over tighten the screw, or vertically with the four Screws (1) provided, four holes, secure the mounting bracket screw holes for the bracket; you will need above the top of the post or rail. Pre-drill the

are straight and level. For the best results, make sure the brackets

Make sure the rain gauge will sit slightly

Once you have fully assembled your rain

Sounting the Rain Gauge:

gauge near a fence or small structures to act

. To prevent distorted readings, place the rain

drive rainfall against the rain gauge and will

such as wind can influence your readings up

Inaccurate readings can occur, and factors

Factors to Consider:

When there are high winds, they tend to

as a buffer.

.ti llit ton

to 20%.

gauge, locate where you want to attach your

rain gauge, preferably a post or rail.

and risk cracking them.

the height of the nearest tree or building.

Rain Gauge at least twice as far away from

A good rule of thumb is to place the Adir Pro
A

the rain from collecting in your gauge

.spnibliud

This guarantees that nothing will obstruct

open area away from trees, shrubs, and

your rain gauge, ensure it is installed in an

• To achieve the most accurate readings from

Gauge" on where to place your brackets and

Bracket 3 (F). Refer to "Mounting the Rain

Next, locate Bracket 1 (D), Bracket 2 (E), and

as it does not snap into place but rather

Do not force the funnel onto the rain gauge

Funnel Lid (C) on top of the Outer Tube (A).

· Take the Outer Tube (A) and place the Inner

Scondly Instructions:

Tube(B) inside of it. Once secured, place the

Parts and Hardware

A. Outer Tube D. Bracket 1

B. Inner Tube E. Bracket 2

C. Funnel Lid F. Bracket 3

Parts

(D)

B

(A)

Rain Gauge Placement:

how to secure them.

rests on top.

Hardware

1. Screws(x4)

(c)

(E)

(F)

0

Ο

0


0

Ο

0

 \bigcirc

ADIPR500-01-BLK **QUICK START** GUIDE





ADIR pro

Limited Warranty:

- 1. Adir Pro (the company) warrants to the purchaser that the product will be free from defects in workmanship and materials for a period of one (1) year from the date of purchase.
- 2. These warranties are not assignable or transferable to any other person.
- 3. Any damage to the product as a result of misuse, tampering, abuse, neglect, accident, improper installation, modification, unauthorized service, destruction, or the alteration of the serial number, or use violate of the instructions furnished by the Company will void this warranty.
- 4. The sole responsibility of the Company shall be limited to the repair or replacement (in its sole discretion) of any component of the product which fails to conform to this warranty at no cost to the purchaser for the period of the warranty.
- 5. Contact the Company directly to obtain service under this warranty. If it becomes applicable to send a defective product to the Company, a Return Authorization Number must first be obtained from the company. In order to obtain service under this warranty, purchaser must provide the Company with the following items (a) proof of purchase, (b) police or fire department report, (c) photographs of damaged sad, and (d) written testimonial.
- Products shipped without prior Return Authorization and Return Authorization Number may not be a accepted, and the Company will not be responsible for their disposition and/or cost of return to the owner.
- 7. The Company will not assume any responsibility for any loss or damage incurred in shipping. All return authorized products should include a copy of the original invoice in order that this warranty may be Honored.

- 8. This warranty is not an insurance policy. The Company is not resposible for any manner of damage to \ or theft of the Purchaser's products or it's contents.
- 9. We recommend that the product being returned is accompanied by the sales receipt with all relevant information regarding the purchase of the item and is returned to the Company within ten (10) days of the claim date of purchase to validate this warranty.
- 10. Any implied warranties that the purchaser may have are limited to the duration of the warranties described above. There are no further warranties that extend or apply beyond the face hereof, and the company expressly disclaims and excludes any and all warranties of merchantability or fitness for a particular purpose. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.
- 11. Repair or replacement shall be the sole remedy for the purchaser under this warranty. The company shall not be liable for any direct, indirect, incidental or consequential damages, losses or expense arising from the use or misuse of the product. Some states do not allow the exclusion or limitations of incidental or consequential damages, so the limitation may not apply to you.
- 12. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Disclaimer:

By purchasing products from Adir Pro, user agrees as follows:

TO THE MAXIMUM EXTENT PERMITTED BY LAW, THE PRODUCTS AND INFORMATION ON THIS SITE IS PROVIDED "AS IS" AND WITH ALL FAULTS AND ADIR PRO. MAKES NO PROMISES, REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, WITH RESPECT TO THE PRODUCTS AND INFORMATION, INCLUDING ITS CONDITION, ITS CONFORMITY TO ANY REPRESENTATION OR DESCRIPTION, OR THE EXISTENCE OF ANY LATENT OR PATENT DEFECTS, AND ADIR PRO. SPECIFICAL-LY DISCLAIMS ALL IMPLIED (IF ANY) WARRANTIES OF TITLE, MERCHANTABILITY, NON INFRINGEMENT, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OR COMPLETENESS, QUIET ENJOYMENT, AND QUIET POSSESSION. THE ENTIRE RISK ARISING OUT OF USE OR PERFORMANCE OF THE PRODUCTS AND INFORMATION LIES WITH USER.

TO THE MAXIMUM EXTENT PERMITTED BY LAW, IN NO EVENT SHALL ADIR PRO PRODUCTS OR ITS SUPPLIERS BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL, INDIRECT, OR EXEMPLARY DAMAGES WHATSOEVER ARISING OUT OF OR IN ANY WAY RELATING TO THIS AGREEMENT OR USER'S USE OF OR INABILITY TO USE THE PRODUCTS AND INFORMATION, OR THE PROVISION OR FAILURE TO PROVIDE SUPPORT SERVICES, INCLUDING, BUT NOT LIMITED TO, LOST PROFITS, LOSS OF CONFIDENTIAL OR OTHER INFORMATION, BUSINESS INTERRUPTION, PERSONAL INJURY, LOSS OF PRIVACY, FAILURE TO MEET ANY DUTY (INCLUDING OF GOOD FAITH OR REASONABLE CARE), NEGLIGENCE, COSTS OF PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR ANY OTHER CLAIM FOR PECUNIARY OR OTHER LOSS WHATSOEVER, OR FOR ANY CLAIM OR DEMAND AGAINST USER BY ANY OTHER PARTY, EVEN IF ADIR PRO HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THESE LIMITATIONS SHALL APPLY NOTWITHSTANDING ANY FAILURE OF ESSENTIAL PURPOSE OF ANY LIMITED REMEDY. NOTWITHSTANDING ANY DAMAGES USER MAY INCUR FOR ANY REASON WHATSOEVER (INCLUDING, WITHOUT LIMITATION, ALL DAMAGES REFERENCED ABOVE AND ALL DIRECT OR GENERAL DAMAGES), THE ENTIRE LIABILITY OF ADIR PRO AND ANY OF ITS SUPPLIERS UNDER ANY PROVISION OF THIS AGREEMENT AND YOUR EXCLUSIVE REMEDY FOR ALL OF THE FOREGOING SHALL BE LIMITED TO THE GREATER OF THE AMOUNT ACTUALLY PAID FOR THE PRODUCTS AND INFORMATION OR U.S. \$1. THE FOREGOING LIMITATIONS, EXCLUSIONS, AND DISCLAIMERS SHALL APPLY TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, EVEN IF ANY REMEDY FAILS ITS ESSENTIAL PURPOSE. If any provision of this Agreement is declared invalid or unenforceable, the remaining provisions of this Agreement will remain in effect. Adir Pro has the right to modify these terms and conditions at any time.